


EXT-POE2H

Extender EXT-POE2 in hermetic enclosure



CODE: **EXT-POE2H** v1.1/II
TYPE: **Extender EXT-POE2 in hermetic enclosure**

EN



Features:

- The output voltage range 44-57 V DC
- Power from PoE switch
- The PoE IN input compliant with the IEEE802.3af/at standard
- The PoE OUT 1/2 output compliant with the IEEE 802.3af standard
- Increases Ethernet and PoE power range by 100 meters
- Designed for 10 Mbit/s and 100 Mbit/s network
- Pole mounting option (requires the OZB2 adapter - optional accessory)
- LED optical signalization
- protections:
 - surge protection (PoE input)
 - OLP overload protection
 - SCP short circuit protection
 - IP56 hermetic enclosure
- warranty – 1 year from the production date

DESCRIPTION

The **EXT-POE2H extender** is a device designed to increase the PoE and Ethernet range by additional 100 meters using UTP Cat. 5 cable. The Extender can be powered using a PoE switch or another PoE-compliant device (PoE IN input). The output voltage and data are available at the PoE OUT1 and OUT2 outputs designed for connecting cameras or other IP devices using PoE power supply. The maximum load current is 0,3 A (total=0,4 A max.).

TECHNICAL DATA

Supply voltage	compliant with 802.3af/at (44+57 V DC)
Current consumption by PSU systems	<30 mA
Module power	20 W max.
Output voltage	compliant with 802.3af
Output current	0,3 A/port ($\Sigma=0,4$ A max.)
Overload protection OLP Short circuit protection SCP	150 % ÷ 200 % of nominal output current, automatic recovery
LED operation indication	Yellow LAN LED - indicating the LAN connection status Green PoE LED - presence of input/output voltage
Range of operating temperatures	-25 °C÷+50 °C
External dimensions	W=198, H=148, D=78 [÷/÷ 2 mm]
Ø cables	6÷13 mm
Connectors: - IN/OUT PoE	RJ45 8P8C
Net/gross weight	0,55 kg / 0,62 kg
Storage temperature	-25 °C...+60 °C
Declarations, warranty	CE, 1 year from the production date