

DS-2CD2212-I5 1.3MP EXIR Bullet Network Camera



EXIR



Key features

- Up to 1.3 megapixel (1280 x 960) resolution
- HD real-time video
- DWDR & 3D DNR
- EXIR illuminators: up to 50m
- IP66
- PoE
- Bracket included

Dimensions



Unit: mm

| DS-2CD2212-I5 | |
|-----------------------------|--|
| Camera | |
| Image sensor | 1/3" progressive scan CMOS |
| Min. illumination | 0.01 lux@F1.2, AGC on 0 lux with IR |
| Shutter time | 1/25s (1/30s) ~ 1/100,000s |
| Lens | 12mm@F2.0, angle of view: 22° (4mm, 6mm optional) |
| Lens mount | M12 |
| Day & night | ICR |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | Digital WDR |
| Backlight compensation | Yes, zone configurable |
| Compression standard | |
| Video compression | H.264 / MJPEG |
| H.264 compression profile | Main profile |
| Bit rate | 32 Kbps ~ 16 Mbps |
| Dual stream | Yes |
| Image | |
| Max. image resolution | 1280 x 960 |
| Frame rate | 50Hz: 25fps (1280 x 960), 25fps (1280 x 720) 60Hz: 30fps (1280 x 960), 30fps (1280 x 720) |
| Image settings | Saturation, brightness, contrast adjustable through client software or web browser |
| Network | |
| Network storage | NAS |
| Alarm trigger | Motion detection, tampering alarm |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1X, QoS, IPv6 (SIP optional) |
| System compatibility | ONVIF, PSIA, CGI |
| General functionalities | User authentication, watermark |
| Interface | |
| Communication interface | 1 RJ45 10M / 100M ethernet port |
| General | |
| Operating conditions | -30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing) |
| Power supply | 12 VDC ± 10%, PoE (802.3af) |
| Power consumption | Max. 7W (9W with ICR on) |
| Ingress protection | IP66 |
| EXIR range | up to 50m |
| Dimensions | 105 x 104.8 x 263.1 mm |
| Weight | 700g (1.5 lbs) |

Available models

DS-2CD2212-I5

* Product picture and technical specs subject to change without previous notice.
For further information, please contact our local sales representatives.