

DS-2FP2020

Security Microphone

HIKVISION
First Choice for Security Professionals

- High Sensitivity microphone, Omnidirectional Pickup, Clear Voice, Strong Anti-jamming capability
- Built-in lightning protection, reverse polarity protection
- RoHS Compliant
- CE & FCC Compliant



Specification

| Model | DS-2FP2020 |
|------------------------|--|
| Spec | |
| Pickup Range | 70m2 |
| Transmission Distance | 3000 Meters |
| Sensitivity | -34dB |
| Frequency Response | 20Hz~20KHz |
| Type | Omnidirectional |
| SNR | 60dB(1Mi 40 db Sound Src SPL) 40dB(10Mi 40 dB Sound Src SPL)1KHz at 1 Pa |
| Dynamic Range | 70dB(1KHz at Max dB SPL) |
| Maximum Sound Pressure | 100dB SPL (1KHz, THD 1%) |
| Output Impedance | 600 Ohm Unbalanced |
| Output Amplitude | 2.5Vpp/-25dB |
| Mic Type | Omnidirectional Microphone |
| Signal Processing | ANC Ambient Noise Cancellation Technology |
| Protection | 30KV Air contact ESD、Lightning Protection, Reverse Polarity Protection |

| | |
|---------------------|--|
| Driver Capability | Built-in pre-amp can directly drive headphones |
| Connection | 3 Leads (Power, Audio, Ground) |
| Cable Type | 3 Conductor Shielded Cable 0.5mm RVVP |
| Voltage | DC12V Power Supply |
| Current | 25mA |
| Working Temperature | -25°C~70°C |
| Color | White / Dark Blue |
| Material | PVC |
| Dimensions | Φ 78mm×28mm |
| Weight | 82 Grams |
| Standards | European CE, US FCC and ISO9000 |