


# C6 KEYSTONE JACK FTP 50u



## Performance:

Meets C6 EIA/TIA 568B Standard.

## Materials:

Body : Fireproof ABS UL-94V0

Metallic Case : Metal

Jack : 8P8C 50 micro inches gold plated

PCB : FR-4 / UL-94V0

IDC Cap : Fireproof PC

IDC Body : Fireproof ABS UL-94V0

IDC Pin : Phosphor Bronze & Tinned

Lock Bar : Metal (SPCC)

IDC Description : For 22-26 AWG.

For 110 or Krone punch-down Tool  
Tooless (when use IDC cap directly)

## Electrical Specifications:

Insulation Resistance : 500M ohms (min.)

Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps .

DC Resistance : 0.1 ohms (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

## Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

|   |          |            |                             |
|---|----------|------------|-----------------------------|
| DRAW NO:  |          | ITEM NO:   | <b>TA8768STZ-WH</b>         |
|  | APPR     | CUSTOMER:  |                             |
| UNIT:<br>m/m  | DESIGN   | DATE:      | <b>21.4.2014</b>            |
| SCALE:  | Ref. NO: | TOLERANCE: | · ± 1 · X ± 0.2 · XX ± 0.15 |