

DS-KIS602/S#Europe



- IP video intercom kit for villa or house, only one call button
- DS-KD8003-IME1/Surface x1
- DS-KH6320-WTE1 x1
- 4 port standard PoE switch x1
- 16GB TF card x1
- European power supply adaptor included (please mark for other standards when you order)

▪ Specification

System parameters	
Processor	Embedded MCU Processor
Operation system	Embedded Linux Operation System
Display parameters	
Display Resolution	1024 × 600
Display Screen	7-inch colorful TFT screen
Audio parameters	
Audio Compression Rate	64 Kbps
Audio Compression Standard	G.711 U
Audio Input	Built-in omnidirectional microphone
Audio Output	Built-in loudspeaker
Audio Quality	Noise suppression and echo cancellation
Network parameters	
Ethernet	10/100 Mbps Self-Adaptive Ethernet
Network protocol	TCP/IP, RTSP
Device interfaces	
I/O input	4
I/O output	2
General	
Power supply	12 VDC/PoE (IEEE 802.3af)
Power consumption	≤10 W
Working temperature	-40° C to +60° C (-40° F to 140° F)
Working humidity	10% to 95%
Dimension (L x W x D)	200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")
Weight	683 g (with packaging) 355 g (without packaging)
IP protection level	IP65
Memory	128 MB
Dimensions(L × W × H)	98 mm × 99.8 mm × 43.9 mm (3.86" × 3.93" × 1.73")
Door station	
Resolution	1920 × 1080
Lens	1/2.7" CMOS
Door station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Door station	
I/O output	1 relay output
Four-wire	1 four-wire interface (1-ch video input, 1-ch audio input/output, 1-ch power,supply, 1-ch grounding)
Door station	
Power supply	12 VDC
Power consumption	Max. 5W
Working temperature	-10° C to + 55° C (14° F to 131° F)

Working humidity	10% to 90%
Dimensions	128 mm × 42 mm × 24.8 mm
Indoor station	
Operation method	Physical button
Type	7-inch colorful TFT LCD
Resolution	800 × 480
Indoor station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Indoor station	
Power supply	12 VDC
Power consumption	≤5 W
Working temperature	-10° C to + 55° C (14° F to 131° F)
Working humidity	10% to 90%
Dimensions (W × H × D)	195.8 mm × 132.8 mm × 18.39 mm (7.7" × 5.2" × 0.7")

▪ Installation Recommendation

▪ Available Model

DS-KIS602/S/Europe BV

DS-KIS602/S/北欧

▪ Accessory

▪ Optional

DS-KD8003-IME2/N S	DS-KD8003-IME1/S	DS-KD8003-IME1/N S	DS-KD8003-IME1#E U	DS-KD8003-IME1
				

DS-KH6320-delete1



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq