

Technical Data Sheet

Product name :Ftth Box - 4cores
(Indoor) Product Number : DINBOX 4N

Application

- Optical Telecommunication System, LAN , Optical fiber Communication System
- Optical fiber testing machine /test equipment
- CATV Networks, Fiber optical transducer
- Optical fiber broadband access network, FTTH access network
- Optical fiber ODF, Rack and wall mount fiber optical distribution frame

Features

- Accommodation of 4 adapters
- Easy installation
- Suitable for SC sx and LC dx adapters
- Optimal for 40 mm/1mm ss wire splicing sleeve.



Products description

- Suitable for Din-rail .
 - Embedded box , installation and removal easily with a protective door ,proof dust.
- Any logo can be printed on the box according to customer requirements
- With the panel suitable for optical fiber SC/LC simplex , duplex mounted in different environments whether in visible or flushed.
- Customers can choose the modules which you like.
- All the modules are free from weld;

Technical Data Sheet

Technical specifications

Item	Technical parameters
Applicable scope	Indoor Cable
Fiber Diameter	125μm (G 652 & G657)
Tight Buffer Diameter	250μm & 900μm
Applicable mode	SM&MM
Tensile strength	>50 N
Operating temperature	-40~+85℃
Adapter type	SC & LC
Insertion Loss	≤0.2dB (1310nm & 1550nm)
Dimensions (LxWxH)	95x61x31.5(mm)

